

# ***micron 5***



***The classic with top functions  
for diverse fields of applications!***

**NEW:**

***High-quality HBC buttons!***

***Frequency management!***



***version!***

***User identification!***

***Vibration alarm!***

***... and much more!***

**DECT**  
Option



***Quality in Control.***



# micron 5



## Highlights:



### Rotary switch

The micron 5 comes standard with rotary switch plus 10 two-step HBC push buttons. The transmitter thus offers an enormous range of functions for diverse fields of applications.



### Ex version (optional)

The micron 5 is available in a special version for Ex zones Underground / 1 / 2 / 21 / 22, opening up numerous additional fields of application.



### User identification (optional)

The HBC Smart Card protects the control from unauthorized use. It enables the blocking of safety-relevant functions for non-authorized personnel as well as the storage of useful operational data.



### Vibration alarm

This function is triggered by low battery level. As an option, it can be used for feedback information such as warnings of impending overloads.



### Frequency management (optional)

A fully automated frequency management via DECT or 2.4 GHz technology ensures interruption-free radio operation without frequency conflicts.

## Carrying methods:



Hip belt.



Optional:  
shoulder strap, carrying bag.

## Applications:

Industrial cranes, machinery and much more.



micron 5.

## Further details:

- 10 two-step HBC push buttons plus rotary switch (inactive if not ordered) / STOP impact switch.
- LED for indication of operating / battery status.
- radiomatic® iLOG for the quick activation of a spare transmitter.
- 2 rechargeable NiMH exchange batteries, approx. 30 hours of continuous operating time (standard version).
- Robust plastic housing, protection class IP 65.
- Weight: 550 g (1.2 lbs.) including battery and rubber shock absorber.
- Manual frequency switch.
- Further options: radiomatic® AFS (Automatic Frequency Selection), catch-release, tandem operation, radiomatic® infrakey, radiomatic® shock-off / zero-g (roll-detect in preparation), pre-selection of trolley / hoist, customized labeling.